

Introduction to ISIS



ISP Workshops

ISIS

- Intermediate **S**ystem to **I**ntermediate **S**ystem
- ISO 10589 specifies OSI IS-IS routing protocol for CLNS traffic
 - A Link State protocol with a 2 level hierarchical architecture
 - Type/Length/Value (TLV) options to enhance the protocol
- RFC 1195 added IP support
 - Integrated IS-IS
 - I/IS-IS runs on top of the Data Link Layer

ISIS

- Known as a Link State Routing Protocol
 - The other link state routing protocol is OSPF
 - Each node in the network computes the map of connectivity through the network
- The other type of Routing Protocol is Distance Vector
 - Like EIGRP or RIP
 - Each node shares its view of the routing table with other nodes

ISIS

- Routers with ISIS enabled on them look for neighbouring routers also running ISIS
 - Hello Protocol Data Units (PDUs) are exchanged
 - The “Hello” packet includes the list of known neighbours, and details such as “hello interval” and “router dead interval”
 - Hello interval – how often the router will send Hellos
 - Router dead interval – how long to wait before deciding router has disappeared
 - The values of “hello interval” and “router dead interval” **must** match on both neighbours
 - When a neighbouring router responds with matching details, a **neighbour relationship** is formed

ISIS Neighbour Relationships

- A relationship is formed between neighbouring routers for the purpose of exchanging routing information
 - This is called an **ADJACENCY**

ISIS Adjacencies

- ❑ Once an adjacency is formed, neighbours share their link state information
 - Information goes in a **Link State PDU** (LSP)
 - LSPs are flooded to all neighbours
- ❑ New information received from neighbours is used to compute a new view of the network
- ❑ On a link failure
 - New LSPs are flooded
 - The routers recompute the routing table

ISIS across a network

- ❑ All routers across the network form neighbour relationships with their directly attached neighbours
- ❑ Each router computes the routing table
- ❑ Once each router has the same view of the network, the network has **converged**
- ❑ The IGP design for a network is crucially important to ensure **scalability** and **rapid convergence**
- ❑ Generally: **the fewer the prefixes, the faster the convergence**

ISIS Levels

- ISIS has a 2 layer hierarchy
 - Level-2 (the backbone)
 - Level-1 (the edge)
- A router can be
 - Level-1 (L1) router
 - Level-2 (L2) router
 - Level-1-2 (L1L2) router
- Most small to medium networks (up to ~400 routers) can happily exist in Level-2

ISIS


- ISIS is multiprotocol
 - Integrated ISIS carries CLNS and IPv4 address families
 - RFC5308 adds IPv6 address family support
 - RFC5120 adds multi-topology support
- ISIS extended to carry IPv6 prefixes
 - Either sharing topology with IPv4
 - When IPv4 and IPv6 topologies are identical
 - Or using “multi-topology”, independent of IPv4
 - Allows incremental rollout of IPv6

Links in ISIS

- Two types of links in ISIS:
 - Point-to-point link
 - Only one other router on the link, forming a point-to-point adjacency
 - Multi-access network (e.g. ethernet)
 - Potential for many other routers on the network, with several other adjacencies
- ISIS in multi-access networks has optimisations to aid scaling
 - One router is elected to originate the LSPs for the whole multi-access network
 - Called “**Designated Information System**”
 - Other routers on the multi-access network form adjacencies with the DIS

Designated IS


- There is ONE designated router per multi-access network
 - Generates network link advertisements
 - Assists in database synchronization
 - Scales ISIS for multi-access (ethernet) networks



Selecting the Designated Router

- ❑ Configured priority (per interface)
 - Configure high priority on the router to be the DIS

```
interface gigabitethernet0/1
isis priority 127 level-2
```
- ❑ Else priority determined by highest MAC address
 - Best practice is to set two routers to be highest priority – then in case of failure of the DIS there is deterministic fall back to the other



Adjacencies: Examples

- To find CLNS adjacency state, use:

```
show clns neighbor
```

System Id	Interface	SNPA	State	Holdtime	Type	Protocol
Router2	Fa0/0	ca01.9798.0008	Up	23	L2	M-ISIS
Router3	Se1/0	*HDLC*	Up	26	L2	M-ISIS

- To find ISIS adjacency state, use:

```
show isis neighbor
```

System Id	Type	Interface	IP Address	State	Holdtime	Circuit Id
Router2	L2	Fa0/0	10.10.15.2	UP	24	Router2.01
Router3	L2	Se1/0	10.10.15.6	UP	27	00

ISIS on Cisco IOS

- ❑ Starting ISIS in Cisco's IOS

```
router isis as42
```

- Where "as42" is the process ID

- ❑ ISIS process ID is unique to the router

- Gives possibility of running multiple instances of ISIS on one router
- Process ID is not passed between routers in an AS
- Some ISPs configure the process ID to be the same as their BGP Autonomous System Number

ISIS NSAP Address

- ❑ IP based routing protocols have the router-id to uniquely identify a router
- ❑ ISIS uses the NSAP address
 - Can be from 64 to 160 bits long
- ❑ ISPs typically choose NSAP addresses thus:
 - First 8 bits – pick a number (usually 49)
 - Next 16 bits – area
 - Next 48 bits – router loopback address
 - Final 8 bits – zero
- ❑ Example:
 - NSAP: 49.0001.1921.6800.1001.00
 - Router: 192.168.1.1 (loopback) in Area 1

ISIS in Cisco IOS

- ❑ Cisco IOS default is for all routers to be L1L2
 - This is suboptimal – all routers need to be L2 only
- ❑ Once ISIS is started, other required configuration under the ISIS process includes:
 - Capture adjacency changes in the system log
`log-adjacency-changes`
 - Set metric-style to wide
`metric-style wide`
 - Set IS type to level 2 only (router-wide configuration)
`is-type level-2-only`
 - Set NET address
`net 49.0001.<loopback>.00`

Adding interfaces to ISIS

- To activate ISIS on an interface:

```
interface POS4/0
  ip router isis as42
```

- Puts interface subnet address into the LSDB
- Enables CLNS on that interface

- To disable ISIS on an interface:

```
router isis as42
  passive-interface GigabitEthernet 0/0
```

- Disables CLNS on that interface
- Puts the interface subnet address into the LSDB

- No ISIS configuration for an interface


- No CLNS run on interface, no interface subnet in the LSDB

ISIS interface costs

- ❑ All interfaces have a default metric of 10
 - Fine for a uniform network, but most backbones have different link capacities between routers & PoPs
- ❑ Many operators develop their own interface metric strategy
 - ```
isis metric 100 level-2
```
  - Sets interface metric to 100
  - Care needed as the sum of metrics determines the best path through the network
- ❑ **ISIS will load balance over paths with equal total cost to the same destination**


# ISIS Metric Calculation

- Best path cost = 11




# ISIS Metric Calculation

- Best path cost = 11



- Equal cost paths = 15



# ISIS Neighbour Authentication

---

- ❑ Neighbour authentication is highly recommended
  - Prevents unauthorised routers from forming neighbour relationships and potentially compromising the network
- ❑ Create a suitable key-chain

```
key chain isis-as42
 key 1
 key-string <password>
!
```

- ❑ Apply key-chain to interface

```
interface POS 4/0
 isis authentication mode md5 level-2
 isis authentication key-chain isis-as42 level-2
!
```

# Other ISIS Features

---

## ❑ Originating a default route into ISIS:

```
router isis as42
 default-information originate
```

- Which will originate a default route into the ISIS LSDB if a default route exists in the RIB

## ❑ ISIS on point-to-point ethernet:

- DIS election is not needed on a point to point link – so it is disabled, which is more efficient

```
interface fastethernet0/2
 isis network point-to-point
```

# Handling IPv6 in ISIS

---

- To add IPv6 support in ISIS:

```
interface POS4/0
 ipv6 router isis as42
```

- Topologies:

- For single topology, nothing else is required
- For multi-topology, include:

```
router isis as42
 address-family ipv6
 multi-topology
```

# Conclusion

---

- ISIS is a Link State Routing Protocol
- Quick and simple to get started
  - But has a myriad of options and features to cover almost all types of network topology
  - ISPs keep their ISIS design **SIMPLE**
  - ~400 routers in a single area is entirely feasible



# Introduction to ISIS



ISP Workshops